CorDEX



Intrinsically safe and rugged handportable **LED Worklight**.

FEATURES



Intrinsically Safe Handportable LED Lantern



54 Lightweight and rugged, IP54



Five superbright LEDs. Powered by interchangeable **EXIS™** battery



Wide coverage; 124° horizontal x 110°vertical



ATEX Certified Zone 1 IIC T4




Up to 3 hours runtime

CorDEX reserve the right to make

New CorDEX portable, Intrinsically Safe Lighting solutions transform the market with best in class functionality, Zone 1 interchangeable battery pack and world-renowned ruggedness.

The Cordex Genesis Portable Worklight is ATEX certified for Zone 1 IIC T4 hazardous locations and is powered by the revolutionary EXIS 740 interchangeable, hot swappable battery pack, meaning a simple change of battery right there in the hazardous area for virtually unlimited runtime.

ATEX certified GENESIS lighting products are rigorously tested to ensure maximum reliability. The smart EXIS powerpacks have on-board energy level indication, along with a bluetooth enabled battery diagnostic station, providing you with data relating to your battery health, charge state and much more all via a dedicated PC application.











	>	
<i>></i>		
	<u> </u>	

Ex ib op is IIC T4 Gb (Ta = -10°C to +40°C) ExVeritas 15 ATEX 0010 X ExVeritas 15 ATEX 0009 U IECEX EXV 15.0009X 400 Up to 3 hrs on one battery 54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
ExVeritas 15 ATEX 0009 U IECEX EXV 15.0009X 400 Up to 3 hrs on one battery 54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
IECEX EXV 15.0009X 400 Up to 3 hrs on one battery 54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
400 Up to 3 hrs on one battery 54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
Up to 3 hrs on one battery 54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
54 Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
Box dimensions 215mm x 235mm x 300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
300mm Five LEDs each operating at up to 1W powered by constant current driver 25000 hours (not replaceable)	
powered by constant current driver 25000 hours (not replaceable)	
Intrinsic Safaty "ih"	
Intrinsic Safety "ib"	
EN60079-02012+A11:2013 and EN 60079- 11:2012	
Gas Zones 1 and 2	
Aluminium with toughened glass lighting window	
T4 (T135C)	
-10°C to 40°C	
1.9kg (with battery)	



On board battery charge status and health information available in the field



PC based Bluetooth diagnostics provides detailed battery information for maximum usability

CorDEX

FOR PRODUCT INFORMATION AND TO PLACE AN ORDER CONTACT:

TEL: +44 (0) 1642 454373

TEL USA: 1 877 836 0764

EMAIL: SALES@CORD-EX.COM

WEB: WWW.CORD-EX.COM

CORDEX INSTRUMENTS LTD.

UNIT 1 OWENS ROAD

SKIPPERS LANE

INDUSTRIAL ESTATE

MIDDLESBROUGH

TS6 6HE

FEATURED PRODUCT

GENESIS LANTERN FL4700